

Machine Supplied in the UK & Ireland by:



[www.vantagehouse.com](http://www.vantagehouse.com)

72 High Street, Brighton

East Sussex, BN2 1RP

Tel: 01273 645000

Fax: 01273 645009

## **USER GUIDE**

# **PREFAMAC ENROBING ATTACHMENT**

## **USERS GUIDE TO THE PREFAMAC ENROBER ATTACHMENT**

### **ASSEMBLING THE ENROBER BELT**

Firstly the chocolate chute should be removed from the moulding machine, along with the vibrating table.

The enrober belt is delivered with all components assembled on it. It should simply be placed on the moulding machine. The ON/OFF-switch for the enrober belt is located on the motor. The enrober belt runs independently of the main machine.

At the top of the machine there are two plastic stoppers (one left, one right) By removing these stoppers the heating lamps can be placed in the holes. Secure the lamps in place with the screws. The heating lamps are plugged into the sockets on the ends of the moulding machine.

### **USING THE ENROBER**

When running the enrober the chocolate wheel must be turning in an anti-clockwise direction. The enrober must be positioned so that the chocolate wheel fits into the slot on the veil box.

The amount of chocolate flowing into the veil box is adjusted by means of a slide under the veil box. Adjust the chocolate curtain by moving the two slides on the veil box.

The vibrator is adjusted by means of the large black knob with the locking arm on the side of the enrober. The position of the blower can be adjusted by sliding it up and down the support rods, and locking it in place using the screws.

To adjust the position of the de-tailer arm simply rotate the de-tailer motor until the correct height is achieved.

The position of the take-off table is adjusted by means of the two screws at the edge closest to the enrober. The tension can be altered by means of the two screws at the far end of the take-off table.

To clean the enrober simply remove the motor, blower and the de-tailer; the rest of the enrober can be placed in water.